



SAFETY DATA SHEET

SETCRETE RAPID SET DPM HARDENER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SETCRETE RAPID SET DPM HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hardener.

Uses advised against None

1.3. Details of the supplier of the safety data sheet

Supplier F.Ball and Co. Ltd.
Churnetside Business Park,
Station Road,
Cheddleton,
Leek,
Staffordshire. ST13 7RS
Tel: 01538 361633 Mon-Fri 8.30am-5.00pm (Exc Bank Holidays)
E.mail: msds@f-ball.co.uk

1.4. Emergency telephone number

Emergency telephone 01538 361633 Mon-Fri 8.30am - 5.00pm (excluding Bank Holidays)

National emergency telephone number UK - National Poisons Information Service Call 111
Ireland - National Poisons Information Centre Call +353 1 809 2166

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Human health The product contains a sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals. This product can cause burns,

Environmental Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictograms



Signal word

Danger

SETCRETE RAPID SET DPM HARDENER

Hazard statements	H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P102 Keep out of reach of children. P261 Avoid breathing vapour/ spray. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P313 Get medical advice/ attention.
Contains	TOFA-DimerFA-TETA PAA, Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine, BENZENE-1,3-DIMETHANAMINE, 3-aminomethyl-3,5,5-trimethylcyclohexylamine, N'-(3-AMINOPROPYL)-N,N-DIMETHYLPROPANE-1,3-DIAMINE
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

benzyl alcohol	10-30%
CAS number: 100-51-6	EC number: 202-859-9
	REACH registration number: 01-2119492630-38-0000
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H332	
TOFA-DimerFA-TETA PAA	10-30%
CAS number: 68082-29-1	
Classification	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
2,4,6-tris(dimethylaminomethyl)phenol	10-30%
CAS number: 90-72-2	EC number: 202-013-9
Classification	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	

SECRETE RAPID SET DPM HARDENER

salicylic acid			<1%
CAS number: 69-72-7	EC number: 200-712-3	REACH registration number: 01-2119486984-17-0000	
Classification			
Acute Tox. 4 - H302			
Eye Dam. 1 - H318			
Repr. 2 - H361d			

The full text for all hazard statements is displayed in Section 16.

Composition comments Epoxy hardener in organic solvent

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged skin contact may cause redness and irritation. May cause serious chemical burns to the skin. May cause an allergic skin reaction.
Eye contact	Irritation, burning, lachrymation, blurred vision after liquid splash. May cause serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Toxic gases/vapours/fumes of: Oxides of the following substances: Carbon. Nitrogen.
Hazardous combustion products	Oxides of carbon. Oxides of nitrogen.

SECRETE RAPID SET DPM HARDENER

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid discharge into drains or watercourses or onto the ground. Contain spillages with sand, earth or any suitable absorbent material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Collect spillage in containers, seal securely and deliver for disposal as hazardous waste.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store in closed original container at temperatures between 5°C and 30°C. Store in a cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

benzyl alcohol (CAS: 100-51-6)

DNEL	Workers - Dermal; : 8 mg/kg Workers - Inhalation; : 22 mg/m ³
PNEC	- Fresh water; 1.0 mg/l - marine water; 0.1 mg/l

TOFA-DimerFA-TETA PAA (CAS: 68082-29-1)

DNEL	Workers - Dermal; : 1.1 mg/kg Workers - Inhalation; : 3.9 mg/m ³
-------------	--

SETCRETE RAPID SET DPM HARDENER

PNEC Fresh water; 0.00434 mg/l
marine water; 0.000434 mg/l

2,4,6-tris(dimethylaminomethyl)phenol (CAS: 90-72-2)

DNEL Workers - Dermal; : 0.15 mg/kg
Workers - Inhalation; : 0.13 mg/m³

PNEC Fresh water; 0.084 mg/l
marine water; 0.0084 mg/l

3-aminomethyl-3,5,5-trimethylcyclohexylamine (CAS: 2855-13-2)

DNEL Workers - Inhalation; : 0.073 mg/m³

PNEC - Fresh water; 0.06 mg/l
- marine water; 0.006 mg/l

BENZENE-1,3-DIMETHANAMINE (CAS: 1477-55-0)

DNEL Workers - Dermal; : 0.33 mg/kg
Workers - Inhalation; : 1.2 mg/m³

PNEC Fresh water; 0.094 mg/l
marine water; 0.0094 mg/l

N'-(3-AMINOPROPYL)-N,N-DIMETHYLPROPANE-1,3-DIAMINE (CAS: 10563-29-8)

DNEL Workers - Dermal; : 0.67 mg/kg
Workers - Inhalation; : 3.7 mg/m³

PNEC Fresh water; 0.0092 mg/l
marine water; 0.00092 mg/l

3-aminopropyltriethoxysilane (CAS: 919-30-2)

DNEL Workers - Inhalation; : 59 mg/m³

salicylic acid (CAS: 69-72-7)

DNEL Workers - Dermal; : 2 mg/kg/day

PNEC - Fresh water; 0.2 mg/l
- marine water; 0.02 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Personal protection

Always check applicability with your supplier of protective equipment.

Eye/face protection

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

SETCRETE RAPID SET DPM HARDENER

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.
Hygiene measures	Provide eyewash station. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse.
Respiratory protection	In case of inadequate ventilation use a respirator suitable for organic vapours. Consult respirator manufacturer for specific advice.
Environmental exposure controls	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Yellowish.
Odour	Amine.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	Not determined.
Flash point	Not determined.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	Not applicable.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1 approx. @ 23°C
Bulk density	Not determined.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	Not determined.
Viscosity	750 - 1500 cP @ 23°C
Explosive properties	Not applicable.

SETCRETE RAPID SET DPM HARDENER

Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not determined.
Comments	Information given is applicable to the product in its ready-to-use form.
9.2. Other information	
Other information	None.
Refractive index	Not determined.
Particle size	Not applicable.
Molecular weight	Not determined.
Volatility	Not determined.
Saturation concentration	Not applicable.
Critical temperature	Not determined.
Volatile organic compound	Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	The following materials may react with the product: Acids. Strong alkalis. Strong oxidising agents.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
---	---

10.4. Conditions to avoid

Conditions to avoid	Considerable exothermic reaction can occur when mixed with epoxide resins
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Strong acids. Strong alkalis. Strong oxidising agents.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon. Oxides of nitrogen.
---	---------------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No information available.
Acute toxicity - oral	
Notes (oral LD₅₀)	No specific test data are available.
ATE oral (mg/kg)	3,965.42
Acute toxicity - dermal	
Notes (dermal LD₅₀)	No specific test data are available.
ATE dermal (mg/kg)	11,442.83

SETCRETE RAPID SET DPM HARDENER

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

ATE inhalation (gases ppm) 85,821.19

ATE inhalation (vapours mg/l) 34.96

ATE inhalation (dusts/mists mg/l) 28.61

Skin corrosion/irritation

Skin corrosion/irritation Corrosive to skin. Causes severe burns.

Animal data No specific test data are available.

Human skin model test No specific test data are available.

Extreme pH No specific test data are available.

Serious eye damage/irritation

Serious eye damage/irritation Corrosivity to eyes is assumed.

Respiratory sensitisation

Respiratory sensitisation No specific test data are available.

Skin sensitisation

Skin sensitisation No specific test data are available.

Germ cell mutagenicity

Genotoxicity - in vitro No specific test data are available.

Genotoxicity - in vivo No specific test data are available.

Carcinogenicity

Carcinogenicity No specific test data are available.

IARC carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility No specific test data are available.

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

Aspiration hazard Not relevant.

General information

Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause chemical burns in mouth, oesophagus and stomach.

Skin contact Causes burns. May cause sensitisation by skin contact.

Eye contact May cause chemical eye burns.

SETCRETE RAPID SET DPM HARDENER

Acute and chronic health hazards	This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns. May cause sensitisation by skin contact.
Route of exposure	Skin and/or eye contact Inhalation
Target organs	Eyes Respiratory system, lungs Skin Reproductive organs
Medical symptoms	Chemical burns. May cause discomfort if swallowed. Severe skin irritation.
Medical considerations	Pre-existing eye problems. Skin disorders and allergies. Chronic respiratory and obstructive airway diseases.

Toxicological information on ingredients.

benzyl alcohol

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 1040 mg/kg, Oral, Mouse LD₅₀ 1620 mg/kg, Oral, Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

TOFA-DimerFA-TETA PAA

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rat

2,4,6-tris(dimethylaminomethyl)phenol

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 2169 mg/kg, Oral, Rat

ATE oral (mg/kg) 500.0

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 1030 mg/kg, Oral, Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ 1840 mg/kg, Dermal, Rabbit LD₅₀ >2000 mg/kg, Dermal, Rat

ATE dermal (mg/kg) 1,100.0

3-aminopropyltriethoxysilane

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 1780 mg/kg, Oral, Rat

SETCRETE RAPID SET DPM HARDENER

ATE oral (mg/kg)	500.0
<u>Acute toxicity - dermal</u>	
Notes (dermal LD ₅₀)	LD ₅₀ 4290 mg/kg, Dermal, Rabbit
<u>salicylic acid</u>	
<u>Acute toxicity - oral</u>	
Notes (oral LD ₅₀)	LD ₅₀ 891 mg/kg, Oral, Rat
ATE oral (mg/kg)	500.0
<u>Acute toxicity - dermal</u>	
Notes (dermal LD ₅₀)	LD ₅₀ > 2000 mg/kg, Dermal, Rat

SECTION 12: Ecological information

Ecotoxicity The product should not be allowed to enter drains, sewers or watercourses.

12.1. Toxicity

Toxicity Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish Not determined

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

Acute toxicity - terrestrial Not determined.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not determined.

Short term toxicity - embryo and sac fry stages Not determined.

Chronic toxicity - aquatic invertebrates Not determined.

Ecological information on ingredients.

benzyl alcohol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 460 mg/l, Pimephales promelas (Fat-head Minnow)
LC₅₀, 96 hours: 645 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 230 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 770 mg/l, Pseudokirchneriella subcapitata

SETCRETE RAPID SET DPM HARDENER

Acute toxicity - microorganisms EC₅₀, 24 hours: 390 mg/l, Activated sludge

TOFA-DimerFA-TETA PAA

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 7.07 mg/l, Fish

Acute toxicity - aquatic plants LC₅₀, 72 hours: 1.25 mg/l, Scenedesmus subspicatus

2,4,6-tris(dimethylaminomethyl)phenol

Acute aquatic toxicity

Acute toxicity - fish , : 718 mg/l, Fish
 , : 175 mg/l, Cyprinus carpio (Common carp)

Acute toxicity - aquatic plants , : 84 mg/l, Desmodium subspicatus

Acute toxicity - microorganisms , : 2 mg/l, Activated sludge

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 110 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 23 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 50 mg/l, Scenedesmus subspicatus

Acute toxicity - microorganisms , 18 hours: 1120 mg/l, Activated sludge

3-aminopropyltriethoxysilane

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >934 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 331 mg/l, Daphnia magna

salicylic acid

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1380 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 870 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: > 100 mg/l, Desmodium subspicatus

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

SETCRETE RAPID SET DPM HARDENER

Phototransformation	Not determined.
Stability (hydrolysis)	Not determined.
Biodegradation	Not determined.
Biological oxygen demand	Not determined.
Chemical oxygen demand	Not determined.

12.3. Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Partition coefficient	Not applicable.

12.4. Mobility in soil

Mobility	The product is non-volatile.
Adsorption/desorption coefficient	Not determined.
Henry's law constant	Not determined.
Surface tension	Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

12.6. Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods	Small quantities may be treated with an equivalent quantity of product resin, allowed to cure and disposed of as low hazard waste. Larger quantities should be disposed of as hazardous waste via a licensed waste operator. Product containers must not be re-used without commercial cleaning.
-------------------------	--

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	2735
UN No. (IMDG)	2735
UN No. (ICAO)	2735
UN No. (ADN)	2735

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 3-AMINOMETHYL-3, 5, 5 - TRIMETHYLCYCLOHEXYLAMINE, TOFA-DimerFA-TETA PAA)
Proper shipping name (IMDG)	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 3-AMINOMETHYL-3, 5, 5 - TRIMETHYLCYCLOHEXYLAMINE, TOFA-DimerFA-TETA PAA, Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine)
Proper shipping name (ICAO)	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 3-AMINOMETHYL-3, 5, 5 - TRIMETHYLCYCLOHEXYLAMINE, TOFA-DimerFA-TETA PAA)

SETCRETE RAPID SET DPM HARDENER

Proper shipping name (ADN) AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 3-AMINOMETHYL-3, 5, 5 - TRIMETHYLCYCLOHEXYLAMINE, TOFA-DimerFA-TETA PAA)

14.3. Transport hazard class(es)

ADR/RID class	8
ADR/RID classification code	C7
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

IMDG Code segregation group	18. Alkalis
EmS	F-A, S-B
ADR transport category	2
Emergency Action Code	2X
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations No listing known.

SETCRETE RAPID SET DPM HARDENER

Guidance	Safety Data Sheets for Substances and Preparations.
Authorisations (Annex XIV Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

SECTION 16: Other information

General information	F.Ball and Company Ltd Technical Datasheet.
Key literature references and sources for data	Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure Limits.
Revision comments	Revised classification.
Revision date	08/07/2021
Revision	6
Supersedes date	17/03/2020
SDS status	Approved.
Hazard statements in full	H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H361d Suspected of damaging the unborn child. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.