

# **Gyproc jointing range** A range of professional jointing and filling products



## Guide to jointing products

The tradition of plasterboard jointing has been around for as long as plasterboard itself; and just as plasterboard has developed so has jointing. Changes in techniques and advances in product formulations have improved the process. British Gypsum has been consistent in bringing you developments and launching new products to make your job easier.

Gyproc brings you a jointing range that consists of setting, air-drying and even a range of combined setting and air-drying compounds. So what's the difference?



#### **Setting products**

- Hand applied with low shrinkage and typically used for joint filling stages
- Hardening is not dependent upon atmospheric humidity
- Unsuitable for finish stage as compound may 'dry-out' before properly hardened

#### **Air-drying products**

- Typically applied thinly therefore preferred for secondary filling or finishing stages
- Apply by hand or with the mechanical jointing system
- If used as a filler, time must be given to permit the material to dry to depth, particularly in cold or humid conditions

#### Setting and air-drying combined

- Gyproc Easi-Fill, Easi-Fill 45, Easi-Fill 20 and Easi-Filler combine the traits of both setting and air-drying materials.
- Gyproc Easi-Fill can be hand or machine applied using mechanical jointing system
- Gyproc Easi-Fill product range has lower shrinkage than conventional joint fillers, and considerably lower than joint cements, so you can use them with absolute confidence in a two-stage application

# Guide to jointing

There are a variety of jointing materials available for all stages of jointing, i.e. bedding tapes through to finishing. Product can be applied either by hand or by machines.

#### **Bedding tapes**

- Tapes add strength to the joints and can be either paper or mesh tapes
- For best results tapes should be applied on tapered edge plasterboards in conjunction with Gyproc Joint Filler
- Paper tapes can be applied by hand or with an automatic taper
- FibaTapes are applied by hand and their self-adhesive backing makes them quick to apply

#### Finishing

- After embedding the tapes, the joints should be finished with 2 or 3 coats of finishing compounds
- Finishing products are available in powder and ready-mixed variants
- All Gyproc finishing products can be applied by hand or using quick release boxes

	Jointing stage			
Product selector	Hand taping	Auto taping	Finishing	Boxes
Joint tape	√	$\checkmark$	-	-
Corner tape	✓	-	-	-
FibaTape	✓	-	-	-
Joint Filler	$\checkmark$	-	-	-
Joint Cement	-	√	$\checkmark$	✓
Ready Mix Joint Cement	-	√	$\checkmark$	~
ProMix LITE	-	$\checkmark$	$\checkmark$	$\checkmark$
Easi-Fill range	√	-	$\checkmark$	<b>√</b> ∗

\* Easi-Fill only

## Tapes

## **Gyproc FibaTape range**

- Self-adhesive for easy application
- Faster jointing than paper tape
- Open fabric avoids blisters and bubbles
- CE Certified ETA-09/0075
- All rolls available in 90m x 48mm

#### **Gyproc FibaTape Classic**

- Self-adhesive drywall joint tape

Product code	Size
5200672378	90m x 48mm



Extra sticky drywall joint tape

Product code	Size
5200672381	90m x 48mm

#### Gyproc FibaTape Perfect-Finish

— Ultra-thin drywall joint tape

Product code	Size
5200672379	90m x 48mm

#### Gyproc FibaTape Mold-X

Mould resistant drywall joint tape

Product code	Size
5200672380	90m x 48mm



## Tapes - continued

#### **Gyproc Joint Tape**

- For flat or internal angles on walls
- Pre-creased for ease of application to internal angles
- Greatest resistance to cracking of any joint reinforcement
- For hand or auto taping application

Product code	Size	
5200010243	150m	



- Reinforce 90° external angles
- Paper joint tape strengthened with two corrosion-resistant metal strips
- Can also be used on internal or external angles that are not 90°
- Dispenses straight from the box for convenience on site



Product code	Size	
5200027605	30m	

## Jointing compounds

#### **Gyproc Joint Filler**

- Gypsum-based setting material for bulk filling
- Low shrinkage product for hand application
- Working time of 60 minutes, setting time of 120 minutes

Product code	Size	
5200004445	12.5kg	





## Jointing compounds - continued

#### **Gyproc Joint Cement**

- Air-drying powder for finishing stage
- When applied thinly can dry quickly, dependent upon environmental conditions, i.e. cold or humidity
- Hand applied, or for all application stages with the mechanical jointing system

Product code	Size
5200572326	22.5kg





## Want to save the hassle of mixing?

#### **Gyproc Ready Mix Joint Cement**

- Air-drying ready mixed material for finishing stage
- Ready to use straight from the tub
- Creates less mess than mixing powder
- When applied thinly can dry quickly dependent upon environmental conditions, i.e. cold or humidity
- Hand applied, or for all application stages with the mechanical jointing system

Product code	Size
5200004291	12 litre

## Want more value?

## Gyproc ProMix LITE Joint Cement

- Lightweight so easier and quicker to apply
- Improved workability
- Minimal shrinkage saves time and money
- Easy to sand to a smooth finish

Product code	Size
5200027604	17 litre





#### Recommended by



cottish ecorators ederation





## **Gyproc Easi-Fill range**

#### **Gyproc Easi-Fill**

- Combined air-drying and setting gypsum-based material for bulk filling
- Minimal drying shrinkage on final coat
- Easy to mix, apply and sand
- Hand or machine applied using the mechanical jointing system
- Apply second coat in 140-280 minutes

Product code	Size	Working time
5200572338	5kg	- 60 minutes
5200572331	10kg	60 minutes

## Want to save more time?

#### **Gyproc Easi-Fill 45**

- Ideal for smaller jointing jobs
- High coverage rate with minimal drying shrinkage on final coat
- Easy to mix, apply and sand
- Apply second coat in 80-160 minutes

Product code	Size	Working time
5200572336	10kg	45 minutes

## Need a snagging product?

#### **Gyproc Easi-Fill 20**

- Ideal for snagging after finishing stage
- Ideal for repairing cracks, dents and holes
- Easy to mix, apply and sand
- Apply second coat in 30-45 minutes

Product code	Size	Working time	
5200572347	5kg	20 minutor	
5200572343	10kg	- 20 minutes	

















**Low cost** - plus zero maintenance fees

**One small deposit** - a single payment of £200, no matter how many tools are hired

**Unlimited maintenance** - 24 hour replacement service

Quick sign-up - new accounts set up quickly

**Broad range of tools** - Power Sanders and Power Vacs, alongside the traditional automatic taping tools to support the system approach

# To hire call 0115 984 9148 or to calculate your hire price visit www.gyproctoolhire.co.uk

## Jointing accessories

## Jointing tools

#### **Heavy Duty Mixing Wheel**

- Maximum durability on site
- Makes mixing easier
- Prevents product build-up on bucket walls

Product code	Size

5200160040

#### **Gyproc Jointing Knife**

- Wide blade with ExtraFlex blued steel
- Soft grip handle for comfort

1	8

Product code	Size
5200109364	200mm
5200109365	250mm

#### **Gyproc Jointing Knife**

- Ground and polished steel blades
- Soft grip handle for comfort
- Hammer head metallic end-caps

Product code	Size
5200115669	100mm
5200115308	125mm
5200115196	150mm

#### **Gyproc Long Handled Broad Knife**

- Blade width of 175mm
- For flattening joint tape and removing excess joint cement
- Replacement blades available
- Lightweight

Product code	Size
5200160422	175mm





## Jointing accessories - continued

## **Board fixing**

#### **Gyproc DriWall Adhesive**

- A general-purpose gypsum-based drywall adhesive for fixing plasterboards to masonry walls
- For use on high, medium or low suction backgrounds



Product code	Size	
5200160032	10kg	
5200009469	25kg	

## **Finishing accessories**

#### **Gyproc Drywall Primer**

- General-purpose plasterboard primer for the final preparation of drywall jointed plasterboard prior to decoration
- Equalises suction characteristics and texture of plasterboard liner and jointed areas
- Creates ideal surface for decorating with most paints and wall coverings
- Prevents plasterboards from yellowing

Product code	Size	
5200572329	10 litre	_

# Canal Prover

#### **Gyproc Drywall Sealer**

- Specially formulated primer / sealer for the final preparation of drywall jointed plasterboard prior to decoration
- Dries quickly for decoration with most paints and wall coverings
- Provides vapour control and a superior, durable finish when applied in two coats
- Single coat protects the board surface from subsequent steam stripping

Product code	Size	
5200572330	10 litre	_



## Repair

### **Filling accessories**

#### **Gyproc Plasterboard Patches (assortment)**

- Permanent repair to plasterboard
- Self-adhesive
- Strong metal mesh
- Easy and quick to install

Sales and	#11910
	Terret
1000	200
- Distant	100
	20

Product code	Pack contains 12 patches	
	50 x 50mm	2 Patches
5200429884	100 x 100mm	5 Patches
	150 x 150mm	5 Patches

#### **Gyproc Easi-Filler**

- Multi-purpose filler for plaster and plasterboard
- Adheres to painted surfaces
- Easy to mix, apply and sand
- Low product shrinkage
- Superior coverage
- Apply second coat 80-160 minutes

Product code	Size	Working time
5200616713	1kg	45 minutes
5200616715	5 x 1kg	

## Gyproc Easi-Filler Ready mixed

## Ideal for...

Repairs to plaster and plasterboard

- Use straight from the tub
- Fills deep holes and cracks
- Quick and easy to apply
- NEW Control of the second seco
  - Adheres to painted surfaces
  - Sands to a fine finish

Product code	Size
5200688365	lkg



"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.



Technical enquiries British Gypsum Technical Advice Centre East Leake Loughborough Leicestershire LE12 6HX Telephone: 0115 945 6123 Fax: 0115 945 1616 Email: bgtechnical.enquiries@bpb.com

British Gypsum September 2015 AR-JOINT-DL-15-01

#### british-gypsum.com

