Repair Range

	Trade Pro	ofessional —————		→ Pro Plasterer		
	ESSIFIL 60 TO THE THE PARTY OF	Cyrrice Exiff 20 Exif 20 E	Trictle One Coat Plaster Was to strong to the Coat Plaster Was to strong t	Traction Bonding 60 White the discount of the control of the con	Thistie Undercoat Plaster Under Grown pares Control of	Thiste Finishing Plaster Washing Plaste
Product	Gyproc EasiFill 60 Easy to finish, quick to decorate	Gyproc EasiFill 20 Easy, fast finish for small areas	Thistle One Coat Plaster One bag for undercoat and finishing	Thistle Bonding 60 Deep patches fast	Thistle Undercoat Plaster Larger areas and deep patches	Thistle Finishing Plaster Traditional method for the finest finish
What's it best for?	Up to 6mm deep holes, patches and cracks	Up to 6mm deep holes, patches and cracks	Repairs and patches holes deeper than 5mm	Small patches, repairs or chases deeper than 5mm	Patches, repairs or chases deeper than 5mm	A fine, smooth, durable finish for patches, cracks, repairs and chases up to 6mm deep
What sort of jobs can it do?	Filling around socket boxes, repairing movement cracks, filling knocks or damage to most backgrounds. Patching larger areas of plaster or plasterboard	Filling around socket boxes, repairing movement cracks, filling knocks or damage to most backgrounds. Patching small areas of plaster or plasterboard	Larger repairs on water or impact damaged plaster, filling pipe or cable chases, making block or brick walls ready for decoration	Smaller repairs on water or impact damaged plaster, filling pipe or cable chases, deep holes (built up in coats)	Larger repairs on water or impact damaged plaster, filling pipe or cable chases, deep holes (built up in coats)	To finish a repair job when used on Thistle Bonding 60 or Thistle Undercoat Plaster
How do I finish it?	Sand to a fine, white finish before painting	Sand to a fine, white finish before painting	Trowel to a smooth finish and allow to fully dry before decoration	Apply a finish coat of Gyproc EasiFill 60, Gyproc EasiFill 20 or Thistle Finishing Plaster, following application instructions as required	Apply a finish coat of Gyproc EasiFill 60, Gyproc EasiFill 20 or Thistle Finishing Plaster, following application instructions as required	Trowel to a smooth finish, allow to fully dry before priming and painting
How long does it stay workable?	60 mins	20 mins	90-120 mins	60 mins	90-120 mins	90-120 mins
How quickly can I finish it?	140 mins	30 mins	120 mins	75 min	180 mins	-
How soon can I decorate it?*	1-24 hours	1-24 hours	72 hours	-	-	48 hours
Pack size	10kg bag	5kg bag	12.5kg bag	10kg tub, 12.5kg or 25kg bags	12.5kg bag	12.5kg bag
Suitable backgrounds						
Lightweight blocks, common bricks	Υ	Υ	Υ	-	-	-
Undercoat plaster	Υ	Y	Υ	Y	Y	Υ
Dense blocks	Υ	Y	Υ	Y	Y	-
Plasterboards and Glasroc boards	Y	Y	Y	Y	Y	Υ
Concrete	Y	Y	Y	Υ	Υ	Υ
Painted surfaces	Y	Y	Υ	Y	Y	Υ
Metal lathing	-	-	Υ	Υ	Y	-
Thistle Bond-it may be required for repairs on smooth/low suction such as dense blocks, MR boards, concretes and painted surfaces. Thistle GypPrime may be required for very high suction backgrounds such as undercoat plaster.						

^{*}Dependent on environmental conditions



