

Gyproc® Drywall Sealer

SAFETY DATA SHEET





SAFETY DATA SHEET

Gyproc Drywall Sealer

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Gyproc Drywall Sealer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Sealer.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier British Gypsum
 East Leake
 Loughborough
 Leicestershire
 LE12 6HX
 UK
 T: +44 (0) 115 945 6123
 E: bgtechnical.enquiries@bpb.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 115 945 6123
 8:30am - 5:00pm Monday - Friday (GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Sens. 1 - H317

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.

Gyproc Drywall Sealer

Precautionary statements	P102 Keep out of reach of children. P261 Avoid breathing dust or mist. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Biocide Labelling	Contains 1,2-Benzisothiazol-3(2H)-one, 2-Methyl-2H-isothiazol-3-one, Bronopol, CMIT/MIT (3:1) to prevent microbial deterioration.
Contains	1,2-Benzisothiazol-3(2H)-one, 2-Methyl-2H-isothiazol-3-one, Reaction mass of: 5-Chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-Methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)
Supplementary precautionary statements	P272 Contaminated work clothing should not be allowed out of the workplace. P321 Specific treatment (see medical advice on this label). P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mica	5 - 10%
CAS number: 12001-26-2	
Substance with National workplace exposure limits.	
Classification	
Not Classified	
Titanium dioxide	2 - 5%
CAS number: 13463-67-7	EC number: 236-675-5
	REACH registration number: 01-2119489379-17-XXXX
Substance with National workplace exposure limits.	
Classification	
Not Classified	

Gyproc Drywall Sealer

Bronopol	<0.025%
CAS number: 52-51-7	EC number: 200-143-0
M factor (Acute) = 10	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
Aquatic Acute 1 - H400	
1,2-Benzisothiazol-3(2H)-one	<0.025%
CAS number: 2634-33-5	EC number: 220-120-9
M factor (Acute) = 1	
Classification	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Aquatic Acute 1 - H400	
2-Methyl-2H-isothiazol-3-one	<0.025%
CAS number: 2682-20-4	EC number: 220-239-6
M factor (Acute) = 10	M factor (Chronic) = 1
Classification	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 2 - H330	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1A - H317	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

Gyproc Drywall Sealer

Reaction mass of: 5-Chloro-2-methyl-4-isothiazolin-3-one		<0.0015%
[EC no. 247-500-7] and 2-Methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)		
CAS number: 55965-84-9	EC number: 611-341-5	
M factor (Acute) = 100	M factor (Chronic) = 100	
Classification		
Acute Tox. 3 - H301		
Acute Tox. 2 - H310		
Acute Tox. 2 - H330		
Skin Corr. 1C - H314		
Eye Dam. 1 - H318		
Skin Sens. 1A - H317		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin contact	It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Temporary irritation.

Gyproc Drywall Sealer

Ingestion	May cause discomfort if swallowed.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Prolonged contact may cause dryness of the skin.
Eye contact	May be slightly irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	--

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
---------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	None known.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
---	--

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.
--	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not touch or walk into spilled material. Keep unnecessary and unprotected personnel away from the spillage. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Ensure procedures and training for emergency decontamination and disposal are in place. Wash thoroughly after dealing with a spillage.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.
--------------------------------	---

6.4. Reference to other sections

Gyproc Drywall Sealer

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep out of the reach of children. Read and follow manufacturer's recommendations. Keep away from food, drink and animal feeding stuffs. Wear protective clothing as described in Section 8 of this safety data sheet. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Keep container tightly sealed when not in use. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep containers upright. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Mica

Long-term exposure limit (8-hour TWA): WEL 0.8 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Titanium dioxide

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

WEL = Workplace Exposure Limit.

Titanium dioxide (CAS: 13463-67-7)

DNEL Workers - Inhalation; Long term local effects: 10 mg/m³
General population - Oral; Long term systemic effects: 700 mg/kg/day

PNEC Fresh water; 0.184 mg/l
marine water; 0.0184 mg/l
Sediment (Freshwater); 1000 mg/kg
Sediment (Marinewater); 100 mg/kg
Soil; 100 mg/kg
STP; 100 mg/l

8.2. Exposure controls

Gyproc Drywall Sealer

Appropriate engineering controls	Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	According to product specification.
Odour	Characteristic.
Odour threshold	Not available.
pH	9
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Gyproc Drywall Sealer

Upper/lower flammability or explosive limits	Not available.
Vapour pressure	48 hPa @ 20°C (DIN 51640)
Vapour density	Not available.
Relative density	Not available.
Density	Not available.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound 0%

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid freezing. Avoid heat.

10.5. Incompatible materials

Materials to avoid Avoid contact with acids.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Summary Based on available data the classification criteria are not met.

Acute toxicity - dermal

Summary Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Gyproc Drywall Sealer

Summary	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Summary	Based on available data the classification criteria are not met.
<u>Serious eye damage/irritation</u>	
Summary	Based on available data the classification criteria are not met.
<u>Respiratory sensitisation</u>	
Summary	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Summary	May cause an allergic skin reaction.
<u>Germ cell mutagenicity</u>	
Summary	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Summary	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Summary	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
Summary	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
Summary	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Summary	Based on available data the classification criteria are not met.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Temporary irritation.
Ingestion	May cause discomfort if swallowed.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Prolonged contact may cause dryness of the skin.
Eye contact	May be slightly irritating to eyes.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.
Medical considerations	Skin disorders and allergies.

Toxicological information on ingredients.

Titanium dioxide

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Mouse

ATE oral (mg/kg) 5,000.0

Gyproc Drywall Sealer

Skin corrosion/irritation

Animal data Dose: 0.5 g, 4 hours, Rabbit Erythema/eschar score: Very slight erythema - barely perceptible (1). Not classified.

Serious eye damage/irritation

Serious eye damage/irritation Dose: 57 mg, 1 second, Rabbit Not irritating.

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - Mouse: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative.

Genotoxicity - in vivo Chromosome aberration: Negative.

Carcinogenicity

Carcinogenicity NOEC 50 mg/m³, Inhalation, Rat

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

2-Methyl-2H-isothiazol-3-one

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 120.0

Species Rat

Notes (oral LD₅₀) Toxic if swallowed.

ATE oral (mg/kg) 120.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 242.0

Species Rat

Notes (dermal LD₅₀) Toxic in contact with skin.

ATE dermal (mg/kg) 242.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 0.11

Species Rat

Notes (inhalation LC₅₀) Fatal if inhaled.

ATE inhalation (dusts/mists mg/l) 0.11

Skin corrosion/irritation

Animal data Dose: 0.5 mL, 4 hours, Rabbit Corrosive to skin.

Serious eye damage/irritation

Gyproc Drywall Sealer

Serious eye damage/irritation	Corrosivity to eyes is assumed.
<u>Skin sensitisation</u>	
Skin sensitisation	Buehler test - Guinea pig: Sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Bacterial reverse mutation test: Negative.
Genotoxicity - in vivo	DNA damage and/or repair: Negative.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Two-generation study - NOAEL 69 - 93 mg/kg/day, Oral, Rat P
Reproductive toxicity - development	Maternal toxicity: - NOAEL: 20 mg/kg/day, Oral, Rat Developmental toxicity: - NOAEL: 40 mg/kg/day, Oral, Rat
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEL 250 ppm, Oral, Rat

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute aquatic toxicity

Summary Based on available data the classification criteria are not met.

Chronic aquatic toxicity

Summary Based on available data the classification criteria are not met.

Ecological information on ingredients.

Titanium dioxide

Toxicity	Aquatic toxicity is unlikely to occur.
<u>Acute aquatic toxicity</u>	
Acute toxicity - aquatic plants	NOEC, 72 hours: 1 mg/l, Pseudokirchneriella subcapitata
Acute toxicity - microorganisms	EC ₅₀ , 3 hours: > 1000 mg/l, Activated sludge

2-Methyl-2H-isothiazol-3-one

Acute aquatic toxicity

LE(C)₅₀	0.01 < L(E)C ₅₀ ≤ 0.1
M factor (Acute)	10
Acute toxicity - fish	LC ₅₀ , 96 hours: 4.77 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 0.934 mg/l, Daphnia magna

Gyproc Drywall Sealer

Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: >0.072 mg/l, Skeletonema costatum
Acute toxicity - microorganisms	EC ₅₀ , 3 hours: 41 mg/l, Activated sludge
<u>Chronic aquatic toxicity</u>	
NOEC	0.01 < NOEC ≤ 0.1
Degradability	Non-rapidly degradable
M factor (Chronic)	1
Short term toxicity - embryo and sac fry stages	NOEC, 98 days: 2.38 mg/l, Oncorhynchus mykiss (Rainbow trout)
Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 0.044 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Titanium dioxide

Biodegradation	Not relevant. Substance is inorganic.
-----------------------	--

2-Methyl-2H-isothiazol-3-one

Phototransformation	Air - DT ₅₀ : 14.35 hours
Biodegradation	Water - Degradation 47.6 - 55.8%: 29 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Titanium dioxide

Bioaccumulative potential	BCF: 19 - 352, Oncorhynchus mykiss (Rainbow trout)
----------------------------------	--

2-Methyl-2H-isothiazol-3-one

Bioaccumulative potential	BCF: 5.75, 48.1, Lepomis macrochirus (Bluegill)
Partition coefficient	log Pow: -0.486

12.4. Mobility in soil

Mobility No data available.

Ecological information on ingredients.

2-Methyl-2H-isothiazol-3-one

Gyproc Drywall Sealer

Adsorption/desorption coefficient	Koc: 6.4 - 10.0
Henry's law constant	<0 Pa m ³ /mol @ 25°C Calculation method.
Surface tension	68.8 mN/m @ 19.5°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Titanium dioxide

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

2-Methyl-2H-isothiazol-3-one

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Reuse or recycle products wherever possible. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Gyproc Drywall Sealer

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Health and Safety at Work etc. Act 1974 (as amended).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EH40/2005 Workplace exposure limits.

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
IATA: International Air Transport Association.
ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
IMDG: International Maritime Dangerous Goods.
CAS: Chemical Abstracts Service.
ATE: Acute Toxicity Estimate.
LC₅₀: Lethal Concentration to 50 % of a test population.
LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
EC₅₀: 50% of maximal Effective Concentration.
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.


Classification abbreviations and acronyms

Skin Sens. = Skin sensitisation

Gyproc Drywall Sealer

Classification procedures according to Regulation (EC) 1272/2008	Skin Sens. 1 - H317: Calculation method.
Document code	BG-SDS-414
Revision comments	SECTION 2: Hazards identification \ 2.2. Label elements.
Revision date	09/10/2020
Revision	02
Supersedes date	24/10/2019
SDS number	8931
Hazard statements in full	H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.



British Gypsum

Head Office, East Leake,
Loughborough,
Leicestershire, LE12 6HX
T: 0115 945 1000

british-gypsum.com